Lithium Battery

Link5-L Link15-L
Link10-L Link20-L

Product Features

- Flexibility modular design, from 5kWh to 20kWh each battery tower
- IP65 protection degree, suitable for both indoor and outdoor installation
- Mounting handle design, easy lift and installation
- Quick connector and auto battery address setting, save installation time
- Independent BMS and SOC indicator for each module
- Safe LiFePO4 rechargeable battery

Technical Data

Model	Link5-L	Link10-L	Link15-L	Link20-L
Nominal Energy (Wh)	5,120	10,240	15,360	20,480
Nominal Capacity (Ah)	100	200	300	400
Nominal Voltage (V)	51.2			
Operation Voltage Range (V)	40~58.4			
Recommend Charge Current (A)	50	100	150	200
Max. Continuous Charge Current (A)	50	100	150	200
Recommend Discharge Current (A)	50	100	150	200
Max. Continuous Discharge Current (A)	50	100	150	200
Max. Parallel Quantities (pcs)	4 pcs Link5-L modules			
Operation Temperature	Charge Temperature: 0~55°C Discharge Temperature: -20~55°C			
Operation Humidity	20~95%RH (No condensing)			
Protection Degree	IP65			
Dimension (mm)	665Wx478.8H x430D	665Wx687.6H x430D	665Wx932.4H x430D	665Wx1159.2H x430D
Net Weight (kg)	60	120	180	240
Installation	floor mounted			
Certification	IEC62619,CE-EMC, ROHS, UN38.3			
Communication	CAN, RS485			
Cycle Life	6000≥100%DOD, 70%EOL@25°C/0.5C			