

## CERTIFICATE of Conformity EU Council Directive 2014/30/EU Electromagnetic Compatibility

**Certificate No.** : AT1811C400832126-M1  
**Report No.** : 1811C40083212601-M1  
**Applicant** : Zhejiang Chisage New Energy Technology Co., Ltd.  
**Address** : No.1828, Fuqing South Road, Panhuo Street, Yinzhou District, Ningbo City, Zhejiang Province, China, 315000  
**Product Name** : Battery Pack  
**Date** : Apr. 28, 2025  
**Model No.** : MOON10-W-SE  
**Trade Mark** : N/A  
**Rating** : See Page 2  
**Test Standards** : EN IEC 61000-6-2:2019  
EN IEC 61000-6-4:2019

The certificate AT1811C400841126-M1 supersedes the certificate AT1811C400841126 which is withdrawn.

The certificate of conformity is based on an evaluation of a sample of the above-mentioned product. Technical report and documentation are at the applicant's disposal. This is to certify that the tested sample is in conformity with all provisions of Annex II of Council Directive 2014/30/EU, in its latest amended version, referred to EMC Directive. The certificate does not imply assessment of the production and does not permit the use of Lab's logo. The applicant of the certificate is authorized to use this certificate in connection with EU declaration of conformity to Article 15 of the Directive.

Certified by



KingKong Jin



The CE Marking may only be used if all relevant and effective EU Directives are complied with



Shenzhen Anbotek Compliance Laboratory Limited  
Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.  
Tel: (86)755-26066440 Email: service@anbotek.com



## CERTIFICATE of Conformity EU Council Directive 2014/30/EU Electromagnetic Compatibility

**Certificate No.** : AT1811C400832126-M1

**Report No.** : 1811C40083212601-M1

**Attachment:**

**Model List:**

Model: MOON10-W-SE	
Description:	Battery Pack
Total Energy:	10.24kWh
Nominal Capacity:	200Ah
Voltage Range:	44.8~57.6Vdc
Nominal Voltage:	51.2Vdc
Max. Charge Voltage:	57.6Vdc
Constant Charge/ Discharge Current	100/150A
Operation Temperature:	-20°C~55°C
Ingress Protection:	IP20
Weight:	85±5kg
Dimension:	W420xH700xD260mm
Designation:	IFpP56/175/206[16s]M/-20+50/90
SN:	<div style="display: flex; align-items: center;"> <div style="border: 1px solid black; padding: 5px; margin-right: 10px;">                 YYYY-MM             </div> <div style="display: flex; flex-wrap: wrap; gap: 5px;"> </div> </div>