# ATTESTATION
# of conformity with European Directives

| | |
|---|---|
| **BV LCIE CHINA Number** | **N°2466AS05CMMC54794** |
| Product | Hybrid Inverter |
| Reference | Jup-10G2-LE, Jup-8G2-LE, Jup-6G2-LE, Jup-5G2-LE, Jup-3G2-LE |
| Trademark | CHISAGE ESS |
| Issued to | Zhejiang Chisage New Energy Technology Co., Ltd. |
| Address | No. 1828,Fuqing South Road,Panhuo Street,Yinzhou District, Ningbo City, Zhejiang Province, China 315000 |
| Manufacturer | Zhejiang Chisage New Energy Technology Co., Ltd. |
| Address | No. 1828,Fuqing South Road,Panhuo Street,Yinzhou District, Ningbo City, Zhejiang Province, China 315000 |
| Technical characteristics | See below table |

**The submitted sample of the above equipment has been tested according to following European Directive and following standards:**

**LVD Directive 2014/35/EU**

| *Standards* | *Report number* | *Report date* |
|---|---|---|
| IEC 62109-1:2010, EN 62109-1:2010<br>IEC 62109-2:2011, EN 62109-2:2011 | CMCC-ESH-P23110778-1<br>CMCC-ESH-P23110778-2 | 15/05/2024 |

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product

**Shanghai (P.R. China), May 23th, 2024.**

**Product Line Manager**

Robin Wu

**This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document is related to the tested specimen of the described electrical sample.**



LCIE CHINA COMPANY LIMITED
Building 4, No. 518, Xin Zhuan Road, CaoHejing Songjiang High-Tech Park, Shanghai P.R.C (201612)
Tel: +86 21 6195 7000 Fax: +86 21 6195 7001
Eamil:BVLCIEMKT@bureauveritas.com

| Ratings | Jup-3G2-LE | Jup-5G2-LE | Jup-6G2-LE |
|---|---|---|---|
| MPP DC voltage range [V] : | 125-425 | | |
| Max, Input DC voltage [V] : | 500 | | |
| Max, Input DC current [A] : | 17 | 17/17 | 17/17 |
| Battery DC voltage range [V]: | 40-60 | | |
| Max.charge/discharge DC current [A]: | 70 | 120 | 140 |
| Output AC voltage [V] : | 230 | | |
| Max, Output AC current [A] : | 15 | 25 | 30 |
| Rated Output power [VA] : | 3000 | 5000 | 6000 |

| Ratings | Jup-8G2-LE | Jup-10G2-LE |
|---|---|---|
| MPP DC voltage range [V] : | 125-425 | |
| Max, Input DC voltage [V] : | 500 | |
| Max, Input DC current [A] : | 26/26 | |
| Battery DC voltage range [V]: | 40-60 | |
| Max.charge/discharge DC current [A]: | 190 | 210 |
| Output AC voltage [V] : | 230 | |
| Max, Output AC current [A] : | 40 | 50 |
| Rated Output power [VA] : | 8000 | 10000 |



LCIE CHINA COMPANY LIMITED
Building 4, No. 518, Xin Zhuan Road, CaoHejing Songjiang High-Tech Park, Shanghai P.R.C (201612)
Tel: +86 21 6195 7000 Fax: +86 21 6195 7001
Eamil:BVLCIEMKT@bureauveritas.com