# ATTESTATION
# of conformity with European Directives

| | |
|---|---|
| **BV LCIE CHINA Number** | **N°2466AS07CMCC55885** |
| Product | Hybrid inverter |
| Reference | Jup-10G2-LE, Jup-8G2-LE, Jup-6G2-LE, Jup-5G2-LE, Jup-3G2-LE |
| Trademark | CHISAGE ESS |
| Issued to | Zhejiang Chisage New Energy Technology Co., Ltd. |
| Address | No. 1828,Fuqing South Road,Panhuo Street,Yinzhou District, Ningbo City, Zhejiang Province, China 315000 |
| Manufacturer | Zhejiang Chisage New Energy Technology Co., Ltd. |
| Address | No. 1828,Fuqing South Road,Panhuo Street,Yinzhou District, Ningbo City, Zhejiang Province, China 315000 |
| Technical characteristics | See below table |

**The inverter(s) is/are tested according the IEC 61727:2004, IEC 62116:2014, IEC 61683:1999, EN 61683:2000, DIN EN 61683:2000 procedure for measuring efficiency.**

| *Standards* | *Report number* | *Report date* |
|---|---|---|
| **IEC 61727:2004**<br>**IEC 62116:2014**<br>**IEC 61683:1999**<br>**EN 61683:2000**<br>**DIN EN 61683:2000** | **CMCC-ESH-P23110777-1**<br>**CMCC-ESH-P23110777-2**<br>**CMCC-ESH-P23110777-3** | **2024-07-06** |

**At the time of issue of this certificate, the representative product listed above corresponds to the stated rules and standards.**

**Shanghai (P.R. China), July 6th, 2024.**

Robin Wu

**Product Line Manager**

**This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document, are related to the tested specimen of the described electrical sample.**



LCIE CHINA COMPANY LIMITED
Building 4, No. 518, Xin Zhuan Road, CaoHejing Songjiang High-Tech Park, Shanghai P.R.C (201612)
Tel: +86 21 6195 7000 Fax: +86 21 6195 7001
Eamil:BVLCIEMKT@bureauveritas.com

| Model / Type.....: | Jup-3G2-LE | Jup-5G2-LE | Jup-6G2-LE |
|---|---|---|---|
| Battery Input Data | | | |
| Battery Voltage [V d.c.] .....: | 40-60 | | |
| Max. charging current [ A ].....: | 70 | 120 | 140 |
| Max. discharging current [ A ].....: | 70 | 120 | 140 |
| PV string Input Data | | | |
| Max. Input DC Voltage [V d.c.].....: | 500 | | |
| MPP DC Voltage Range [V d.c.] .....: | 125-425 | | |
| Max. Input DC Current [A d.c.].....: | 17 | 17+17 | 17+17 |
| Output AC Voltage [V a.c.].....:..... | 1L/N/PE 230, 50/60Hz | | |
| Output AC Rated Current [A a.c.].....: | 13,65 | 22,7 | 27,3 |
| Max. Output AC Current [A a.c.].....: | 15 | 25 | 30 |
| Rated Output Power [W a.c.].....: | 3000 | 5000 | 6000 |
| Max. Output AC Power [VA a.c.].....: | 3600 | 6000 | 7200 |

| Model / Type.....: | Jup-8G2-LE | Jup-10G2-LE |
|---|---|---|
| Battery Input Data | | |
| Battery Voltage [V d.c.] .....: | 40-60 | |
| Max. charging current [ A ].....: | 190 | 210 |
| Max. discharging current [ A ].....: | 190 | 210 |
| PV string Input Data | | |
| Max. Input DC Voltage [V d.c.].....: | 500 | |
| MPP DC Voltage Range [V d.c.] .....: | 125-425 | |
| Max. Input DC Current [A d.c.].....: | 26+26 | 26+26 |
| Output AC Voltage [V a.c.].....:..... | 1L/N/PE 230, 50/60Hz | |
| Output AC Rated Current [A a.c.].....: | 34,5 | 45,5 |
| Max. Output AC Current [A a.c.].....: | 40 | 50 |
| Rated Output Power [W a.c.].....: | 8000 | 10000 |
| Max. Output AC Power [VA a.c.].....: | 9600 | 12000 |

**This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document, are related to the tested specimen of the described electrical sample.**



LCIE CHINA COMPANY LIMITED
Building 4, No. 518, Xin Zhuan Road, CaoHejing Songjiang High-Tech Park, Shanghai P.R.C (201612)
Tel: +86 21 6195 7000 Fax: +86 21 6195 7001
Eamil:BVLCIEMKT@bureauveritas.com